



MI-270b

- NOTES:**
1. CIRCUIT SHOWN STARTS WITH SN5651, AND APPLIES ONLY TO PC BOARD #9750 (MAIN BOARD) AND PC BOARD #9730 (OUTPUT BOARD).
 2. D105, D205, D106 AND D206 ARE LOCATED ON THE MAIN BOARD (SHOWN ON OUTPUT BOARD FOR CLARITY).
 3. ALL RESISTORS ARE IN OHMS, ALL CAPACITORS ARE IN MICROFARADS, UNLESS OTHERWISE NOTED.
 4. OUTPUT PC BOARD #9730 CONTAINS COMPONENTS FOR BOTH CH#1 AND CH#2, AND IT IS LOCATED ON THE FRONT PANEL HEAT SINK ASSEMBLY.
 5. LED 102 AND 202 ARE LOCATED ON THE OUTPUT PC BOARD.
 6. SW1 IS SHOWN IN STEREO POSITION.
 7. THE BALANCED INPUT DOES NOT FUNCTION WHEN UNBALANCED INPUT IS USED.
 8. BEGINNING WITH SN5651 DECOUPLING NETWORK (R7) AND C10, 11, 12 (SEE MI-270a) WERE REMOVED.
 9. BEGINNING WITH SN5651, LOCATION OF C3 ALTERED AS SHOWN. IN ADDITION, R8 (2.7 ohm) WAS PLACED IN PARALLEL WITH C3.

THIS IS A REPRESENTATIVE SCHEMATIC ONLY AND DOES NOT NECESSARILY REFLECT THE EXACT CIRCUITRY OF YOUR UNIT. PLEASE REFER TO THE RESPECTIVE SERVICE MANUAL FOR SPECIFIC TECHNICAL INFORMATION.

