



7761 He

MODIFICATIONS RESERVES

ALTERATIONS RESERVED

VOLTAGES MEASURED TO CHASSIS WITH GRUNDIG-VTVM AT 20V AC MEASURING VALUES VALID FOR [BC FM] WITHOUT INPUT SIGNAL

REMARKS:
 TUNING EYE SERVICE MEASURED A CHASSIS AVEC GRUNDIG-VTVM ET 20V CA (TUNING EYE SERVICE UNIT MEASURES FROM [BC FM])
 OBSERVATIONS TENSION MESURE PAR RAPPORT A LA CARTE AVEC GRUNDIG-VTVM ET 20V CA

USE RATINGS: TR - 25V - 8.5A (NORMAL) 210W - 8.5A (RESISTIVE)

MAINS RELEASE: 110...220V-50/60 Hz

WAVE RANGES:
 60 LW 95 ... 250 KC
 60 MC 5M ... 100 MC
 60 SW 5.8 ... 100 MC
 FM 87 ... 100 MC

COMPONENTS:
 250V PAPER
 500V PAPER
 500V PAPER
 175V ROUSTY PAPER
 500V CERAMICS
 1/2W
 1/2W
 1/2W
 1W
 WIRE RESISTOR
 RESISTANCE IN OHMS

WARRANTY:
 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 22. 23. 24. 25. 26. 27. 28. 29. 30. 31. 32. 33. 34. 35. 36. 37. 38. 39. 40. 41. 42. 43. 44. 45. 46. 47. 48. 49. 50. 51. 52. 53. 54. 55. 56. 57. 58. 59. 60. 61. 62. 63. 64. 65. 66. 67. 68. 69. 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.

GRUNDIG WERKE FURTH (BAY.)
AM/FM Super 2220 NL

(11-1208-2101/S)