



TABLE OF VOLTAGES

COMPONENT	TYPE	ELECTRODE	TEST POINT	IN SQUARE	VOLTS
V1	Mazda VP210	Anode (v/c max)	7	21 N	62
		Anode (v/c min)	7	21 N	95
		Screen (v/c max)	8	9 G	50
		Screen (v/c min)	8	9 G	78
V2	Mazda HL2	Anode	16	4 G	38
		Anode	26	2 D	110
V3	Mazda Pen231	Anode	11	2 E	108
		Screen	29	26 L	-10
H.T.-Plug					

Total Current (v/c max) 6.8 M.a.
(v/c min) 6.25 M.a.

TABLE OF COMPONENTS

B3 I

CODE	VALUE	TEST		SQUARE	CODE	VALUE	TEST		SQUARE	CODE	VALUE	TEST		SQUARE
		From	To				From	To				From	To	
C1A	500pF	4	10	18 M	R1	100,000	1	2	12 H	L4	4	7	13	8 C
C1B	500pF	7	10	18 N	R2	1MΩ	6	31	3 C	L5	12	12	13	8 D
C2	500pF	3	10	10 B	R3	100,000	8	11	5 E	L6	1.25	14	16	7 C
C3	0.1μF	6	10	12 G	R4	20,000	11	12	4 E	L7	6.5	14	15	7 D
C4	Trimmer	4	10	19 N	R5	2MΩ	9	17	5 H	L8	5	16	18	3 H
C5	0.1μF	8	10	6 F	R6	100,000	11	20	3 D	L9	2	18	19	3 H
C6	Trimmer	7	10	19 N	R7	2,000	11	25	4 C	L10	50	19	20	3 H
C7	2.25μF	10	11	6 E	R8	150	10	22	2 C					
C8	0.1μF	10	12	6 C	R9	150	22	24	2 C					
C9	100pF	7	17	7 F	R10	850	24	29	2 B	T1 Prim	190	21	22	24 L
C10	300pF	10	15 16	7 A	R19	100,000	22	29	4 A	Sec.	600	23	24	
C11	225pF	10	19	3 G						T2 Prim	414	25	26	25 R
C12	0.1μF	20	21	6 F	L1	15	2	3	12 C	Sec.	0.15	10	27	
C13	0.002μF	25	26	3 C	L2	4	4	5	12 B					
C14	125pF	16	18	4 H	L3	12	5	6	12 B					